Philips
PAL coax cable

10 m

> 50 dB Male to Male

SWV2803W

Ensure a reliable connection

with this PAL type coaxial cable

Depend on this cable to provide you with a reliable audio/video connection between components.

Enjoy good picture quality
- Nickel-plated connectors for reliable contact

Enjoy good audio quality
- High purity copper conductor for reliable signal transfer

Protects against signal loss
- Bare copper shielding

Easy installation
- Non-slip ergonomic grip for easy use

Enjoy extended durability
- Molded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief

PHILIPS

sense and simplicity

PAL coax cable
10 m > 50 dB Male to Male

SWV2803W/10

Specifications

Packaging dimensions
- Packaging dimensions (W x H x D): 16.0 x 23.6 x 3.0 cm
- Nett weight: 0.296 kg
- Gross weight: 0.308 kg
- Tare weight: 0.012 kg
- EAN: 87 12581 37868 4
- Number of products included: 1
- Packaging type: Card

Outer Carton
- Outer carton (L x W x H): 57.2 x 26.7 x 17.8 cm
- Nett weight: 3.552 kg
- Gross weight: 4.590 kg
- Tare weight: 1.038 kg
- EAN: 87 12581 37875 2
- Number of consumer packagings: 12

Inner Carton
- Inner carton (L x W x H): 24.9 x 17.8 x 15.2 cm
- Nett weight: 1.184 kg
- Gross weight: 1.330 kg
- Tare weight: 0.146 kg
- EAN: 87 12581 37874 5
- Number of consumer packagings: 4

Product highlights

Bare copper shielding
Bare copper shielding protects against signal loss.

Easy grip
This non-slip grip makes connecting your components easy and ergonomically comfortable.

Flexible PVC Jacket
Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

High purity copper
This copper conductor provides high accuracy in signal transfer with minimal resistance.

Molded plug
Molded plugs ensure secure connections between components and offer extended durability.

Nickel-plated connectors
Nickel-plated connectors establish a clean contact between the cable and connector for a reliable connection.

Rubber strain relief
Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.

Issue date 2008-09-26
Version: 1.0.13
12 NC: 8670 000 35372
EAN: 87 12581 37868 4

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.
Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com